



BELZONA®
3111
FLEXIBLE MEMBRANE

**The Long Term Solution to
All Roof Leaks**

Roof problems result from roof movement caused by constant weather changes. The sun, wind, frost, rain, snow and pollutants all contribute to roof degradation.

Belzona® 3111 (Flexible Membrane) provides impermeability to liquids, but permeability to water vapor - allowing the roof to breathe. Besides productivity reductions, leaking roofs cause damage to equipment, costly interior redecoration, degradation of the building's structure, fire risks due to electrical shortage, and ruined stock and delivery delays. Belzona® 3111 (Flexible Membrane) offers:

- **VERSATILITY IN USE**
- **WEATHERTIGHT ROOFING**
- **FIRE PROTECTION**
- **LONG TERM LIGHTWEIGHT PROTECTION**
- **EASY REPAIR WHEN DAMAGED**

Only Belzona has the proven solution for protection of all types and shapes of roofing substrates:

- **UPSTANDS**
- **GLAZING BARS**
- **ASPHALT**
- **FLASHINGS**
- **SKYLIGHTS**
- **CHIMNEYS & VENTS**
- **MULTI-SUBSTRATES**
- **LEAD - ZINC - COPPER**
- **COPING STONES & PARAPET WALLS**
- **GUTTERS**
- **ASBESTOS**
- **JOINTS**
- **SEAMS**
- **FELT**



GUTTERS



GLAZING BARS



JOINTS



ASPHALT



SKYLIGHTS



MULTI-SUBSTRATES

The Unconventional Alternative.

Belzona Polymerics Ltd. Harrogate, HG1 4AY, England
Fax: +44 (0) 1423 505967 • Tel: +44 (0) 1423 567641
E-mail: Com@Belzona.co.uk

Belzona Inc. Miami, Florida 33172, USA
Fax: (305) 599-1140 • Tel: (305) 594-4994
E-mail: Belzona@Belzona.com





BELZONA® 3000 SERIES POLYMERIC MEMBRANES

Economy in Use

- Five year minimum shelf life when stored as directed.
- Partially used containers can be resealed for future use.

Simplicity in Use

- No skilled labor needed. Easy brush application.
- Equipment readily washes out with a detergent solution.

Safety in Use

- No solvent content; no health risk; no offensive smells.
- No heat required.
- No fire risk; no increase in insurance premiums.

Versatility in Use and Application

- Follows roof contours no matter how complex.
- Highly elastic; adapts to roof movements.
- Available in light grey or white.



AVAILABLE IN 15 LITERS (4 GALLON)
UNIT SIZE

Accessories

- Belzona® 3911 (PSC Surface Conditioner) – A one part, solvent-based surface conditioner for use on porous and bituminous surfaces such as concrete, masonry, wood, asphalt, and mineral felt.
- Belzona® 3921 (GSC Surface Conditioner) – A two part, solvent-based surface conditioner for use on porous or non-porous surfaces. The high zinc content makes this product suitable for application to galvanized metal surfaces, and steel protection applications.
- Belzona® 9311 (Reinforcing Sheet) – A man-made specially woven, open mesh fabric, provides added durability, and should be used in virtually all Belzona® 3111 applications. It also acts as a film thickness gauge.



BS EN ISO 9002 - 1994
Certificate No. Q/09335



BRITISH BOARD OF
AGREEMENT
Certificate No. 86/1752

